

Oljerekommendationer och oljevolymer

Backslag Volvo Penta

Motorbeteckning	Oljetyp	Viskositet	Oljevolymer
RB (<i>gemensamt oljerum med motorn</i>)	Motorolja av mineraltyp	SAE15W-40	-
MS, MSB	Motorolja av mineraltyp	SAE15W-40	0,6 L
MS2, MS2B-A, MS2B-L, MS2A-D, MS2L-D	Motorolja av mineraltyp	SAE15W-40	0,8 L
MS2A-E, MS2L-E	Syntetisk transmissionsolja	SAE75W-90	0,8 L
MS2V	Motorolja av mineraltyp	SAE15W-40	1,8 L
MS3, MS3B, MS3C	Motorolja av mineraltyp	SAE15W-40	1,6 L
MS4A, MS4B	Syntetisk transmissionsolja	SAE75W-90	1,7 L
MS5A, MS5B, MS5C	Syntetisk transmissionsolja	SAE75W-90	1,7 L
MS10A, MS10A-B, MS10L, MS10L-B	ATF Dexron III	-	0,4 L
MS15A, MS15A-B, MS15L, MS15L-B	ATF Dexron III	-	0,6 L
MS25A, MS25L	ATF Dexron III	-	0,75 L
HS1, HS1A, HS1E-A	Motorolja av mineraltyp	SAE15W-40	3,0 L
HS25A	ATF Dexron III	-	1,8 L
HS45A, HS45AE, HS45AE-B	ATF Dexron III	-	2,5 L
HS63A, HS63AE, HS63AE-B, HS63AE-C, HS63IVE	ATF Dexron III	-	3,8 L
HS63V, HS63VE	ATF Dexron III	-	4,3 L
HS80AE, HS85AE	ATF Dexron III	-	5,0 L
HS80IVE, HS85IVE	ATF Dexron III	-	7,0 L
PRM	Motorolja av mineraltyp	SAE15W-40	-
ZF	Motorolja single grade	SAE30	-
Twin Disc	Motorolja single grade	SAE30	-